



CORDAGE APPLICATIONS:

- Motor Controls
- In-Plant Power Distribution

CHARACTERISTICS 60°C, 600 Volt

- UL Standard 62
- CSA Standard C22.2 No.49

- Jacket: Black Neoprene
- Conductor: Stranded Bare Copper
- Insulation: Color-Coded Rubber
- Color Code: Black, White, Green, Red

Catalog Number	Cable Type/AWG	Conductors			Draht x Ø	Thickness(mm)	AußenØ	Weight/km	UPE		
		AWG No. mm ²			Stranding	Insul. Jacket	O.Dia.	Cu(kg)Net	Packed		
1934	SO 18/2	18	2	0.81	16x0.254	0.76	1.52	9.1	15	99	76m
1934/3	SO 18/3	18	3	0.81	16x0.254	0.76	1.52	9.6	22	112	76m
1934/4	SO 18/4	18	4	0.81	16x0.254	0.76	1.52	10.4	30	142	76m
1935	SO 16/2	16	2	1.32	26x0.254	0.76	1.52	9.6	24	115	76m
1935/3	SO 16/3	16	3	1.32	26x0.254	0.76	1.52	10.2	36	143	76m
1935/4	SO 16/4	16	4	1.32	26x0.254	0.76	1.52	11.2	48	172	76m
1936	SO 14/2	14	2	2.08	41x0.254	1.14	2.03	13.4	38	208	76m
1936/3	SO 14/3	14	3	2.08	41x0.254	1.14	2.03	14.1	57	252	76m
1936/4	SO 14/4	14	4	2.08	41x0.254	1.14	2.03	15.2	76	308	76/30m