



TYPE SR GRIP-TITE(R) STRAIN RELIEF CONNECTORS

Malleable Iron Body and Gland Nut, Nylon Gripper, Neoprene Grommet, PVC or Buna-N Sealing Ring, Steel Locknut

Zinc Plated On Body, Gland Nut & Locknut

- ◆ UL Listed and CSA Certified
- ◆ Liquidtight, oiltight, raintight
- ◆ Rated at 90°C
- ◆ Suitable for NEMA 4 enclosures and other wet locations

NPT	Catalog No.	Cat.No. 90°	Cord Range	UL Standard 514, CSA Standard C22.2#18, NEC Articles 400-10 and 400-14, NEMA Standards FB1-1983, Fed. Spec. W-C-586c, Mil. Spec. 100 and 130
1/2	SR-50-250	SR-950-250	4.0- 6.4mm	Suitable for use in Hazardous Locations under NEC 501-4(b), 502-4(a) (2), and 503-3(a). For Class I Div. 2, Class II, Div. 1 and 2, and Class III, Div. 1 and 2.
1/2	SR-50-375	SR-950-375	6.4- 9.5mm	
1/2	SR-50-500	SR-950-500	9.5-12.7mm	
3/4	SR-75-250	SR-975-250	4.0- 6.4mm	Suitable for use in Hazardous Locations under NEC 501-4(b), 502-4(a) (2), and 503-3(a). For Class I Div. 2, Class II, Div. 1 and 2, and Class III, Div. 1 and 2.
3/4	SR-75-375	SR-975-375	6.4- 9.5mm	
3/4	SR-75-500	SR-975-500	9.5-12.7mm	
3/4	SR-75-625	SR-975-625	12.7-15.9mm	
3/4	SR-75-750	SR-975-750	15.9-19.1mm	