



Dimensions
= mm

North American Watertight
Pin and Sleeve Receptacles
(Material: Valox 357)

Listed to UL 1682 and 1686
Certified to CSA Standard C22.2 No. 182.1
IEC Classified to Standards 309-1 & 309-2

Cat# 60A	A	B	C	Cat# 100A	A	B	C	Wiring	Volt AC	Color	Ground
360R4-W	89	48	111	3100R4-W	100	58	122	2p3w	125	Yellow	4h
360R6-W	89	48	111	3100R6-W	100	58	122	2p3w	250	Blue	6h
360R7-W	89	48	111	3100R7-W	100	58	122	2p3w	480	Red	7h
460R12-W	89	48	111	4100R12-W	100	58	122	3p4w	125/250	Orange	12h
460R9-W	89	48	111	4100R9-W	100	58	122	3p4w	3Ø250	Blue	9h
460R7-W	89	48	111	4100R7-W	100	58	122	3p4w	3Ø480	Red	7h
460R5-W	89	48	111	4100R5-W	100	58	122	3p4w	3Ø600	Black	5h
560R9-W	89	48	111	5100R9-W	100	58	122	4p5w	3ØY120/208	Blue	9h
560R7-W	89	48	111	5100R7-W	100	58	122	4p5w	3ØY277/480	Red	7h
560R5-W	89	48	111	5100R5-W	100	58	122	4p5w	3ØY347/600	Black	5h