



60A, 100A Plug

Dimensions

= mm

North American Watertight
Pin and Sleeve Plugs
(Material: Valox 357)

Listed to UL 1682 and 1686
Certified to CSA Standard C22.2 No. 182.1
IEC Classified to Standards 309-1 & 309-2

Cat# 60A	A	B	C	Cat# 100A	A	B	C	Wiring	Volt AC	Color	Ground
360P4-W	275	114	17-41	3100P4-W	312	127	24-48	2p3w	125	Yellow	4h
360P6-W	275	114	17-41	3100P6-W	312	127	24-48	2p3w	250	Blue	6h
360P7-W	275	114	17-41	3100P7-W	312	127	24-48	2p3w	480	Red	7h
460P12-W	275	114	17-41	4100P12-W	312	127	24-48	3p4w	125/250	Orange	12h
460P9-W	275	114	17-41	4100P9-W	312	127	24-48	3p4w	3Ø250	Blue	9h
460P7-W	275	114	17-41	4100P7-W	312	127	24-48	3p4w	3Ø480	Red	7h
460P5-W	275	114	17-41	4100P5-W	312	127	24-48	3p4w	3Ø600	Black	5h
560P9-W	275	114	17-41	5100P9-W	312	127	24-48	4p5w	3ØY120/208	Blue	9h
560P7-W	275	114	17-41	5100P7-W	312	127	24-48	4p5w	3ØY277/480	Red	7h
560P5-W	275	114	17-41	5100P5-W	312	127	24-48	4p5w	3ØY347/600	Black	5h