



60A, 100A Connector

Dimensions

= mm

North American Watertight
Pin and Sleeve Connectors
(Material: Valox 357)

Listed to UL 1682 and 1686
Certified to CSA Standard C22.2 No. 182.1
IEC Classified to Standards 309-1 & 309-2

Cat# 60A	A	B	C	Cat# 100A	A	B	C	Wiring	Volt AC	Color	Ground
360C4-W	286	112	17-41	3100C4-W	325	123	24-48	2p3w	125	Yellow	4h
360C6-W	286	112	17-41	3100C6-W	325	123	24-48	2p3w	250	Blue	6h
360C7-W	286	112	17-41	3100C7-W	325	123	24-48	2p3w	480	Red	7h
460C12-W	286	112	17-41	4100C12-W	325	123	24-48	3p4w	125/250	Orange	12h
460C9-W	286	112	17-41	4100C9-W	325	123	24-48	3p4w	3Ø250	Blue	9h
460C7-W	286	112	17-41	4100C7-W	325	123	24-48	3p4w	3Ø480	Red	7h
460C5-W	286	112	17-41	4100C5-W	325	123	24-48	3p4w	3Ø600	Black	5h
560C9-W	286	112	17-41	5100C9-W	325	123	24-48	4p5w	3ØY120/208	Blue	9h
560C7-W	286	112	17-41	5100C7-W	325	123	24-48	4p5w	3ØY277/480	Red	7h
560C5-W	286	112	17-41	5100C5-W	325	123	24-48	4p5w	3ØY347/600	Black	5h