

Stahlmuffe mit Gewinde für
GRC-IMC Rigid Schutzrohr

Dimensions = mm



GRC-IMC RIGID CONDUIT
THREADED COUPLINGS

ANSI Standard C80.1
UL Standard 6
NEC Article 346
Federal Specification WW-C-581

Size	Catalog Number	Ref.	Outside Diameter	Length	UPE/Pack	Wght.EA	EDP No
1/2	GRC-IMC 1/2	08456	25.7	39.7	100	54g	113021
3/4	GRC-IMC 3/4	08457	31.8	41.3	50	82g	113022
1	GRC-IMC 1	08458	38.7	50.8	30	136g	113023
1 1/4	GRC-IMC 1 1/4	08459	47.5	52.4	25	168g	113024
1 1/2	GRC-IMC 1 1/2	08460	54.7	52.4	25	236g	113025
2	GRC-IMC 2	08461	67.3	54.0	20	327g	113026
2 1/2	GRC-IMC 2 1/2	08462	82.6	79.4	24	772g	113027
3	GRC-IMC 3	08463	98.3	82.6	16	953g	113028
3 1/2	GRC-IMC 3 1/2	08464	114.3	85.7	12	1544g	113029
4	GRC-IMC 4	08465	123.8	88.9	10	1362g	113030
5	GRC-IMC 5	08466	152.4	95.3	Bulk	2157g	113031
6	GRC-IMC 6	08467	182.9	101.6	Bulk	3473g	113032