

Applications: portable heaters, test equipment, high voltage apparatus.  
 Features: flexible test probes, resists oils, acids, alkalines, ozones & solvents.  
 Availability: 1000ft (304m) spools, 500ft (152m) spools, also on bulk reels.



20 or 18 AWG annealed stranded tinned or bare copper,  
 EDPM rubber insulation (-20°C to + 75°C).  
 Available with PUC insulation upon request.

(1) MIL-W-13169  
 (2) UL Style 3357  
 OSHA Acceptable

Cat.No.	AWG	mm <sup>2</sup>	Strand/Dia	Ins/Thick.		NomØ	Working	Brkdwn.	Colors
1004 xxx	20	0.523	41x0.127mm	EPDM	1.016	3.05	1500V	6000V	Black, Red
1001 xxx	20	0.523	41x0.127mm	EPDM	1.194	3.56	3000V	12000V	Black, Red
1002 xxx	18	0.829	65x0.127mm	EPDM	1.143	3.56	5000V	20000V	Black, Blue, Green, Gray, Red
1006 xxx	18	0.829	65x0.127mm	EPDM	2.235	5.84	10000V	29000V	Black, Red
1007 xxx (1)	18	0.829	65x0.127mm	EPDM	1.194	3.68	5000V	20000V	Black, Blue, Green, Gray, Red
1009 xxx (2)	18	0.829	65x0.127mm	EPDM	1.194	3.68	5000V	20000V	Black, Blue, Green, Gray, Red