



Hol-Tite® Oil Tight Hole Seals

Extra pushbutton holes, conduit openings, and knockout openings are sealed against dust, dirt, oil, and water with Hol-Tite® Seals. Seals will cover any size or shape of

hole from .19-inch diameter to maximum diameter shown in table. Can be used on enclosure walls up to .31-inch thick.

Steel Hole Seals

- 12 sizes
- ANSI 61 gray polyester powder paint finish over galvanizing
- Galvanized 16 gauge steel back plate
- Stud (#10-32 x 5/8) and wing nut are zinc plated
- Oil resistant gasket
- UL Component Recognized Type 3R, Type 4, Type 12, and Type 13
- CSA Type 3R, Type 4, Type 12, and Type 13

Stainless Steel Hole Seals

- 8 sizes
- Polished front surface
- Seal, backplate, stud (#10-24 x 5/8) and wing nut are 300 series stainless steel
- 16 gauge stainless steel backplate
- Oil resistant gasket
- UL Component Recognized Type 3R, Type 4, Type 4X, Type 12, and Type 13
- CSA Type 3R, Type 4, Type 4X, Type 12, and Type 13



Steel Catalog Number	Stainless Steel Catalog Number	For	Maximum Hole Diameter	Hol-Tite Diameter
ASBPG	ASBPGSS	22.5mm oil-tight pushbutton holes	0.88 (22)	1.22 (31)
AS050	AS050SS	1/2-inch conduit holes	0.88 (22)	1.38 (35)
AS075	AS075SS	3/4-inch conduit holes	1.06 (27)	1.56 (40)
ASPB	ASPBSS	30.5mm oil-tight pushbutton holes	1.25 (32)	1.75 (44)
AS100	AS100SS	1-inch conduit holes	1.38 (35)	1.88 (48)
AS125	AS125SS	1 1/4-inch conduit holes	1.69 (43)	2.19 (56)
AS150	AS150SS	1 1/2-inch conduit holes	2.00 (51)	2.50 (64)
AS200	AS200SS	2-inch conduit holes	2.50 (64)	3.00 (76)
AS250	—	2 1/2-inch conduit holes	3.00 (76)	3.50 (89)
AS300	—	3-inch conduit holes	3.62 (92)	4.12 (105)
AS350	—	3 1/2-inch conduit holes	4.12 (105)	4.62 (117)
AS400	—	4-inch conduit holes	4.62 (117)	5.12 (130)



Touch-Up Paint

Touch-Up Paint is used to repair the finish of enclosures and panels. Furnished in 12oz. spray cans.

Catalog Number	Color
ATPGRAYX	Gray Epoxy
ATPOSA	OSHA Orange Enamel
ATPHE	Gray Hammertone Enamel
ATPWE	White Enamel
ATPSG	Gray Enamel
ATPHSGP	High Solids Gray
ATPPY61	ANSI 61 Gray for Polyester Powder
ATPDLB	DesignLine Beige Enamel
ATPDLBR	DesignLine Dark Brown Enamel
ATPMG	Light Gray for Polyester Powder
ATPHS61	High Solids ANSI 61 Gray
ATPFG	Light Gray for fiberglass
ATPG7035	RAL 7035 Gray
ATPG7032	RAL 7032 Gray
ATPB7021	RAL 7021 Black
ATPB9005	RAL 9005 Black

Data subject to change without notice