# B\_]\_A Rundumleuchten

# **GYROLASER ROTATING BEACONS**

# **General Specification**

The Gyrolaser is a compact but powerful aerodynamically designed halogen rotating beacon. The units are credited with ECE65, the latest harmonised European standard (compulsory in many Countries) for vehicle warning lights.

A highly polished "Super-beam" reflector fitted with a unique powerstrip out performs other rotating reflector systems. Heavy duty RFI suppressed motors are available in 12V or 24V.

Lenses are injection moulded high impact polycarbonate with a textured top to reduce sun glare. are attached to the base with quick release stainless steel clips that allow easy bulb replacement.

## **Technical Specification**

Lens Colour: Blue, Amber, Red, Green, Clear

Voltage: 12V or 24V Wattage (12V): 55W Wattage (24V): 70W Amp Draw (12V): 4.5Amp Amp Draw (24V): 2.9Amp Rotation Speed: 160/min standard

Length: 158mm (6.2") Width: 135mm (5.3") Height: 108mm (4.25") Low profile design reduces wind resistance

PH02GYRO

U.V. stabilised polycarbonate lens

Anodised alloy base

**ECE65** Certified

### Magnetic and perminant mout versions



#### <u>880</u>

Permanent mount beacon. Availablewith a single bolt or three point fastening. Weight : 0.4Kg (0.9lbs)

#### <u>880M</u>

Magnetic roof mount beacon. Fitted with a heavy duty 3" 90lb pull nickel coated magnet and removable moulded rubber boot for paintwork protection, coiled lead and cigar plug. Weight : 0.9Kg (2.0lbs)

#### **8FL Multi-Flash Mirror**

Injection moulded multi-flash clip-on mirror, suitable for dash or rear shelf mounting, multiple flashes to a brilliant 800 per minute with 160/min rotator.

The hood is designed to eliminate distracting stray light. Weight : 0.21kg (0.1lbs)

#### **8KT Universal Bracket**

A universal mounting bracket supplied with adhesive pads.

#### PCMO Extending Mast

Used mainly on motorcycles the mast is constructed of stainless steel and is fitted with model 880 beacon and coil lead.

Retracted height including the 880 0.71m (28"). Extended height 1.23m (48.5") Weight : 1.9Kg (4.2lbs)

Weitere Typen auf Anfrage. Änderungen vorbehalten. Abmessungen in mm.