


**9936 WeatherProof Exit Sign IP65**

F9936 bulkhead style weatherproof exit sign made from polycarbonate. An economical fitting for general industrial & external environments.

F9936/WP/E Single Sided EXIT 2x8W Polycarbonate body & lens




PHOTOMETRIC CLASSIFICATION		MAXIMUM PERMISSIBLE SPACING FOR EMERGENCY LUMINAIRES															
		MOUNTING HEIGHT - M															
F9936/WP	C0	D3.2	6.5	6.6	6.6	6.5	6.4	6.2	5.8	5.1	4.1						
	C90	E2.5	5.6	5.8	5.8	6.0	5.8	5.8	5.2	5.2	4.6						

**9937 WeatherProof Exit Sign IP67**

F9937 weatherproof exit to IP67 encased in light grey high impact resistant ABS body. An ideal fitting for industrial and exterior applications with adverse ambient conditions.

**SERIES 9937 WEATHER PROOF EXIT SIGN 2 X 8W**  
 F9937/WP/\* Single Sided 2x8W ABS body & lens

- \* Specify EXIT arrows if required:
- /E = EXIT
- /EALR = Arrow left and right
- /EAR = Arrow right
- /EAL = Arrow left




PHOTOMETRIC CLASSIFICATION		MAXIMUM PERMISSIBLE SPACING FOR EMERGENCY LUMINAIRES															
		MOUNTING HEIGHT - M															
F9937/WP	C0	D8	9.4	9.7	9.9	10.1	10.2	10.3	10.4	10.3	10.2	9.5	8.3	6.1			
	C90	C8	6.8	7.2	7.4	7.7	7.9	8.0	8.2	8.3	8.2	7.8	6.9	5.2			

**9938 WeatherProof Exit Sign IP65**

F9938 is a slim larger version of the 9936 Bulkhead. It utilises a 10w maintained fluorescent lamp. Features peel off arrows.

Also available as a 24w PL non-maintained Catalogue Number F9938/WP/PR.

F9938/WP/E Single Sided EXIT 1x10W



PHOTOMETRIC CLASSIFICATION		MAXIMUM PERMISSIBLE SPACING FOR EMERGENCY LUMINAIRES															
		MOUNTING HEIGHT - M															
F9938/WP/E	C0	D3.2	6.5	6.6	6.6	6.5	6.4	6.2	5.8	5.1	4.1						
	C90	E2.5	5.6	5.8	5.8	6.0	5.8	5.8	5.2	5.2	4.6						