


USA - SUPER-FLEX XHHW-2 Power Wire, Class K Stranded

SUPER-FLEX XHHW-2

Product Summary

Extra-Flexible Class K stranded copper conductor. Special cross-linked thermoset-insulation stays flexible to -40°C. For use in applications where extra-flexible power wire is needed, in circuits requiring XHHW-2 rated wire.



- **XLP Thermo-Set Insulation**
- **UL Listed Type XHHW-2**
- **UL 44 Thermoset-Insulated Wire and Cables**
- **AWM 125°C 600V Rated in Wet or Dry Locations**
- **Oil Resistant**
- **RoHS Compliant available**
- **Standard BC (bare copper), Alternate TC (tinned copper) conductor available**
- **Standard Put-Up 500 feet Reels, Request for Special Put-Up's**

Catalog No.	AWG (Stranding)	Conductor Dia. (inches/mm)	Fin. O.D. (inches/mm)	Approx. Fin. Weight (Mft/km)
XHW1403	14 (41/30) BC	0.075 / 1.905	0.138 / 3.5052	18 lbs. / 26.8 kg
XHW1203	12 (65/30) BC	0.100 / 2.540	0.163 / 4.1402	26.5 lbs. / 39.5 kg
XHW1003	10 (105/30) BC	0.125 / 3.175	0.188 / 4.7752	40 lbs. / 59.6 kg
XHW0803	8 (7x24/30) BC	0.175 / 4.445	0.267 / 6.7818	66 lbs. / 98.3 kg
XHW0403	4 (7x59/30) BC	0.260 / 6.604	0.385 / 9.7790	162 lbs. / 241.3 kg
XHW0203	2 (7x95/30) BC	0.330 / 8.382	0.455 / 11.5570	250 lbs. / 372.4 kg
XHW0103	1 (19x44/30) BC	0.375 / 9.525	0.545 / 13.8430	323 lbs. / 481.1 kg
XHW10003	1/0 (19x55/30) BC	0.400 / 10.160	0.570 / 14.4780	395 lbs. / 588.4 kg
XHW20003	2/0 (19x70/30) BC	0.480 / 12.192	0.655 / 16.6370	515 lbs. / 767.1 kg
XHW30003	3/0 (19x88/30) BC	0.495 / 12.573	0.675 / 17.1450	617 lbs. / 919.0 kg
XHW40003	4/0 (7x7x43/30) BC	0.625 / 15.875	0.800 / 20.3200	748 lbs. / 1114.2 kg

Color Code Chart											
01	02	03	04	05	06	07	08	09	10	11	12
Red	White	Green	Blue	Yellow	Brown	Orange	Black	Pink	Gray	Tan	Purple

Technical Data are Subject to Change without Notice.