



Power & Control

The extensive range of power and control accessories is suitable for any residential installation. The range incorporates such features as wide rockers for easy operation, an arc shield, which minimises visible arc flash and positive switching mechanism to prevent balancing between the on and off positions. A product marking service is also available on 13A fused connection units as well as 20A and 45A control switches.



13A SWITCHED SOCKET OUTLETS

LIST NO	DESCRIPTION	CARTON QTY
VX1300	1 gang SP switched socket	10
VX1300/D	1 gang DP switched socket	5
VX1400	1 gang SP switched socket with neon	10
VX1500	2 gang SP switched socket	5
VX1500/D	2 gang DP switched socket	5
VX1600	2 gang SP switched socket with neon	5
VX1700	2 gang DP switched socket with outboard rockers	5
VX1800	2 gang DP switched socket with outboard rockers & neon	5
VT1507	1-2 gang conversion socket	1

- BS1363
- Terminals suitable for up to 3x2.5mm² or 2x4mm² conductors
- 2 gang DP comes with twin earth as standard

Dimensions

- 1 gang: 85mmx85mm with 60.3mm fixing centres
- 2 gang: 145mmx85mm with 120.6mm fixing centres

Mounting boxes

- Surface moulded: 1 gang VX9409; 2 gang VX9414
- Flush metal: 1 gang SB655; 2 gang SB665
- Flush dry lining: 1 gang SB619; 2 gang SB629



13A UNSWITCHED SOCKET OUTLETS

LIST NO	DESCRIPTION	CARTON QTY
VX9100	1 gang unswitched socket	10
VX9200	2 gang unswitched socket	5
VX9230	3 gang unswitched socket, fused 13A	5

- BS1363
- Terminals suitable for up to 3x2.5mm² or 2x4mm² conductors

Dimensions

- 1 gang: 85mmx85mm with 60.3mm fixing centres
- 2 gang: 145mmx85mm with 120.6mm fixing centres
- 3 gang: 205mmx85mm with 181mm fixing centres

Mounting boxes

- Surface moulded: 1 gang VX9409; 2 gang VX9414; 3 gang VX9403
- Flush metal: 1 gang SB655; 2 gang SB665; 3 gang SB646
- Flush dry lining: 1 gang SB619; 2 gang SB629



13A 30mA RCD PROTECTED SOCKETS & FCU

LIST NO	DESCRIPTION	CARTON QTY
VT1108	1 gang switched RCD protected socket outlet	1
VT1208	2 gang switched RCD protected socket outlet	1
VT1092	RCD Fused Connection Unit	1

- Socket outlets to BS7288
- FCU to BS4293
- Double pole switching
- Terminals suitable for up to 3x2.5mm² or 2x4.0mm² conductors

Dimensions

- 1G: 86mmx86mm with 60.3mm fixing centres
- 2G: 146mmx86mm with 120.6mm fixing centres
- FCU: 86mmx86mm with 60.3mm fixing centres

Mounting boxes

- Surface moulded: 1G & FCU: VX9405 2G: VX9417
- Flush metal: 1G & FCU: SB615 2G: SB625



ROUND PIN SOCKET OUTLET

LIST NO	DESCRIPTION	CARTON QTY
VX9900	15A switched socket	10
VX9901	2A 3 pin socket	10
VX9904	16A 2 pin socket (for export only)	10
VX9906	16A 2 pin switched socket (for export only)	10
VX9907	16A 2 pin twin switched socket (for export only)	5

- BS546 (VX9900, VX9901), BS5733

Dimensions

- 1 gang: 85mmx85mm with 60.3mm fixing centres
- 2 gang: 145mmx85mm with 120.6mm fixing centres

Mounting boxes

- Surface moulded: VX9409. Flush metal: SB655



VX1081

VX1090

13A FUSED CONNECTION UNITS WITH OPTIONAL FLEX OUTLET

LIST NO	DESCRIPTION	CARTON QTY
VX1080	DP switched	10
VX1081	DP switched with neon	10
VX1090	Unswitched	10
VX1091	Unswitched with neon	10

- BS1363
- Terminals suitable for up to 3x2.5mm² or 2x4mm² conductors
- Fitted with knockout position at bottom edge of plate
- Cord outlet suitable for flexible cord up to 10mm² diameter

Dimensions
85mmx85mm with 60.3mm fixing centres

Mounting boxes
Surface moulded: VX9409. Flush metal: 1 gang SB655



VX1080WM

FUSED CONNECTION UNIT MARKING SERVICE EXAMPLES

LIST NO	MARKING	CARTON QTY
VX1080BO	BOILER	10
VX1080HD	EXTRACTOR HOOD	10
VX1080DW	DISH WASHER	10
VX1080EF	EXTRACTOR FAN	10
VX1080FR	FRIDGE	10
VX1080FZ	FREEZER	10
VX1080FF	FRIDGE FREEZER	10
VX1080HB	HOB	10
VX1080HT	HEATING	10
VX1080MW	MICROWAVE	10
VX1080TD	TUMBLE DRYER	10
VX1080WD	WASTE DISPOSAL	10
VX1080WDR	WASHER DRYER	10
VX1080WM	WASHING MACHINE	10
VX1080WH	WATER HEATER	10

Marking to customer specification also available



CA1075

CHIMES AND BELLPUSHES

LIST NO	DESCRIPTION	CARTON QTY
CA1075	2 Note Chime with Integral Transformer	1
CA1076	2 Note Chime	1
CA2001	Bell Push	1
CA2001L	Illuminated Bell Push	1

- Chime:
- 8V~
 - Max 85 dB/A

Dimensions
169mmx104mmx49mm

- Bellpush:
- Max 24V

Dimensions
65mmx25mmx20mm

Fixing screws not supplied



VX1013

6A THREE POLE CONTROL SWITCH

LIST NO	DESCRIPTION	CARTON QTY
VX1013	3 pole isolating switch marked with isolator and fan symbol	10

- BS3676, BS EN 60947-3
- 250V only

Dimensions
85mmx85mm with 60.3mm fixing centres

Mounting boxes
Surface moulded: VX9404
Flush metal: 1 gang SB623



VX1060

VX1060WH

20A DP CONTROL SWITCHES WITH OPTIONAL FLEX OUTLET

LIST NO	DESCRIPTION	CARTON QTY
VX1070	DP switch	10
VX1070WH	DP switch marked 'Water Heater'	10
VX1060	DP switch with neon	10
VX1060WH	DP switch with neon marked 'Water Heater'	10

- BS EN 60669-1
- Terminals suitable for 3x2.5mm² or 2x4mm² conductors
- Fitted with knockout position at bottom edge of plate
- Cord outlet suitable for flexible cord up to 10mm²

Dimensions
85mmx85mm with 60.3mm fixing centres

Mounting boxes
Surface moulded: VX9409
Flush metal: SB655



VX1060AC

20A DP CONTROL SWITCH MARKING SERVICE

The following markings are available as standard by adding the appropriate suffix to the list number, eg VX1060**AC**:

AIR CONDITIONING – **AC**
WATER HEATER – **WH**
WASHING MACHINE – **WM**

Markings to customer specification also available



VX5207

VX5208

20A BATH/SINK SWITCH

LIST NO	DESCRIPTION	CARTON QTY
VX5207	20A bath/sink switch with neon	10
VX5208	20A bath/sink switch	10

- BS 3676



45A DP CONTROL SWITCHES

LIST NO	DESCRIPTION	CARTON QTY
VX9712	45A DP switch with neon	1
VX9713	45A DP switch	1
VX9702	45A DP switch with neon (large plate)	1
VX9703	45A DP switch (large plate)	1

- BS EN 60669-1
- Terminals suitable for up to 1x16mm² cable

Dimensions

- 1 gang: 85mmx85mm with 60.3mm fixing centres
- Large plate: 85mmx145mm with 120.6mm fixing centres

Mounting boxes

- Surface moulded: 1 gang VX9405; large plate VX9416
- Flush metal: 1 gang SB618; large plate SB628

- The following markings are available, add the appropriate suffix to the list number, eg VX9712**CK**

COOKER – **CK**

SHOWER – **SH**

AIR CONDITIONING – **AC**



45A COOKER CONTROL UNITS

LIST NO	DESCRIPTION	CARTON QTY
VX9700	45A cooker control unit with 13A switch socket & neon indicators	1
VX9701	45A cooker control unit with 13A switch socket	1

- BS4177, BS1363
- Terminals suitable for up to 1x16mm² cable
- Double pole switching on both 45A & 13A circuits
- 2 earth terminals

Dimensions

- 145mmx85mm with 120.6mm fixing centres

Mounting boxes

- Surface moulded: VX9416
- Flush metal: SB628



COOKER OUTLET PLATE

LIST NO	DESCRIPTION	CARTON QTY
VX9704	Cooker outlet plate with 2x10mm ² pillar terminals	10

• BS5733

Dimensions

85mmx85mm with 60.3mm fixing centres

Mounting boxes

Surface moulded: VX9405

Flush metal: SB615



13A FLEX OUTLET PLATE

LIST NO	DESCRIPTION	CARTON QTY
VX9990	Flex outlet plate with pillar type terminals	10

• BS5733 where applicable

• Suitable for flex up to 10mm²

• Terminals suitable for up to 3x2.5mm² conductors

Dimensions

85mmx85mm with 60.3mm fixing centres

Mounting boxes

Surface moulded: VX9409

Flush metal: SB655



DUAL VOLTAGE SHAVER UNIT

LIST NO	DESCRIPTION	CARTON QTY
VX9800	20VA dual voltage shaver unit	1

• BSEN 61558

• Suitable for bathrooms when installed in accordance with IEE regulations

• 2 socket outlets, with safety shutters, clearly marked 115V or 230V

• Accepts British, Continental or American shaver plugs

• Double wound safety isolating transformer with overload protection

• Terminal suitable for 2x2.5mm² conductors

Dimensions

85mmx145mm with 120.6mm fixing centres

Mounting boxes

Surface moulded: VX9410

Flush metal: SB628



20A DUAL VOLTAGE SHAVER LIGHT UNIT

LIST NO	DESCRIPTION	CARTON QTY
VT7066	20VA dual voltage shaver unit	1

- BSEN60598
- 2 socket outlets, with safety shutters, clearly marked 115V or 230V
- Pull cord switch for operation of 60W lamp
- Accepts British, Continental or American shaver plugs
- Automatic cut-out and reset protects against overload

Dimensions
438mmx72mm



50A DP CEILING SWITCHES

LIST NO	DESCRIPTION	CARTON QTY
VX9706	50A DP ceiling switch with neon and mechanical 'off' indicator	5

- BS EN 60669-1
- Double pole switching
- 60.3mm fixing centres
- Pillar terminals suitable for all cables up to 10mm²
- For ease of wiring, 2 earth terminals are fitted

Mounting box
Surface moulded: VX9405

To learn more about B-I-A please visit us at our
WEB site: www.BiaGmbH.com

