

Plugs, Bases, Sockets & Lampholders

Plug tops



Pack	Cat No.	Colour codes:BL (Black), CL (Clear), GY (Grey), WE (White) Large finger-grip, rigid, impact-resistant moulding, 250V a.c.
10	90	10A plug top, 3 pin flat (BL,WE)
10	90/15	15A plug top, 3 pin flat (BL, GY, WE)
10	90/20	20A plug top, 3 pin flat (GY,WE)
10	90/25	25A plug top, 3 pin, L-shaped earth, flat active and neutral (WE)
10	90R	10A plug top, 3 pin, round earth, flat active and neutral (WE)
10	94	10A plug top, 4 pin plug for use with Cat. No 33 and 34 series. Available in white only (WE)

Pack	Cat No.	Low profile side entry with 45° cord entry and screwed clamp terminals, 250V a.c.
10	106/1	10A plug top, 3 pin flat. (BL, GY, WE)
10	106/2	10A plug top, 3 pin flat, accepts 15A heavy duty flexible cord. (WE)
10	106/3	15A plug top, 3 pin flat (BL, WE)
10	106/4	20A plug top, 3 pin flat (BL, WE, GY)
10	106/5	25A plug top, 3 pin, L-shaped earth, flat active & neutral (WE)
10	106/6	10A plug top, 3 pin, round earth, flat active & neutral (BL, WE, GY)
10	106/7	10A plug top, 3 pin, flat earth, round active & neutral (BL, WE, GY)
10	106/8	32A plug top, 3 pin, U-shaped earth, flat active & neutral (WE)



Pack	Cat No.	Flexible PVC cover with cord locking nut, and screwed clamp terminals, 250V a.c.
10	100L	10A plug top, 3 pin flat, locking nut, 8mm entry hole (BL, CL, GY, WE)
10	100LHD	10A plug top, 3 pin flat, 10mm entry hole for 15A heavy duty cord (CL, GY)
10	100/8	10A plug top, 3 pin flat, figure 8 wire (BL, WE)
10	100R	10A plug top, 3 pin, round earth, flat active & neutral (BL, CL, GY, WE)
10	100/2R	10A plug top, 3 pin, flat earth, round active & neutral (CL, GY, WE)
10	100L15	15A plug top, 3 pin flat (CL, GY, WE)

Plug bases



Pack	Cat No.	Plug bases, surface, 250V a.c. Mounting centres: 50mm. Size 65mm dia x 48mm high. Standard colour is clear.
10	37	10A plug base, 3 pin flat, includes Cat. No. 37B snap-on base plate.
10	37/15	15A plug base, 3 pin flat
10	37R	10A plug base, 3 pin, round earth, flat active & neutral
10	37B	Snap-on base plate for Cat. No. 37 range. Also fits Cat. No. 366, 80 & 33

Plugs, Bases, Sockets & Lampholders



Pack	Cat No.	3 pin plug surface bases, low profile, 250V a.c.
10	35	10A surface base, 3 pin flat (BR, BL, WE)



Pack	Cat No.	Plug base and plate assemblies
Mounting centres: 95mm. Suits standard mounting accessories. Can be mounted horizontally or vertically. Size: 114 x 70mm.		
10	38/1	10A, Cat. No. 38 plug base on plate (BL, RED, WE)
10	38/115	15A, Cat. No. 38/15 plug base on plate (WE)
10	38/1R	10A, Cat. No. 38R plug base on plate (WE)
10	38/120	20A, Cat. No. 38/20 plug base on plate (WE)
10	38/12R	10A, Cat. No. 38/2R plug base on plate (WE)
1	38/1PL	Plate only suit 38 series (WE)



Pack	Cat No.	Plug bases for panel or flush mounting, 250V a.c.
Supplied as base mechanism plus front plate. Size: 38mm dia x 25mm deep. Minimum order quantities may apply - please check prior to ordering		
10	38	10A plug base, 3 pin flat, suits panel thickness of 2.5mm (BL, MG, WE)
10	38A0	10A plug base, 3 pin flat, suits panel thickness of 1.0mm (BL, WE)
10	38A1	10A plug base, 3 pin flat, suits panel thickness of 1.2mm (WE)
10	38A2	10A plug base, 3 pin flat, suits panel thickness of 1.5mm (WE)
10	38A3	10A plug base, 3 pin flat, suits panel thickness of 1.6mm (BL, WE)
10	38A4	10A plug base, 3 pin flat, suits panel thickness of 2.0mm (WE)
10	38A5	10A plug base, 3 pin flat, suits panel thickness of 2.2mm (WE)
10	38R	10A plug base, 3 pin, round earth, flat active & neutral, suits panel thickness of 2.5mm (WE)
10	38/2R	10A plug base, 3 pin, flat earth, round active & neutral, suits panel thickness of 2.5mm (WE)
10	38/15	15A plug base, 3 pin flat, suits panel thickness of 2.5mm (BL, WE)
10	38/20	20A plug base, 3 pin flat, suits panel thickness of 2.5mm (WE)
10	38/25	25A plug base, 2 pin flat with L earth pin, suits panel thickness of 2.5mm (WE)



Pack	Cat No.	4 pin plug surface bases, 250V a.c.
10	33	10A 4 pin plug base with looping terminal. 50mm mounting centres. 69 x 69 x 46mm. (WE)
10	33B	Snap-on base plate for Cat. No. 33 range. 58mm mounting centres. 114 x 70mm. (CL)
10	34B	Snap-on base plate for Cat. No. 34 range. 91mm mounting centres. 150 x 70mm (CL)

Plugs, Bases, Sockets & Lampholders

Extension sockets



Pack	Cat No.	Flexible PVC cover with safety skirt, cord locking nut and screwed clamp terminals, 240V a.c. Colour codes: BL (Black), CL (Clear), GY (Grey), WE (White).
10	7P	10A extension socket, 3 pin flat, 8mm entry hole (BL, CL, GY, WE)
10	7P15	10A extension socket, 3 pin flat, 10mm entry hole (CL, GY, WE)



Pack	Cat No.	Elbow plug socket
10	39	10A elbow plug socket

Ceiling roses



Pack	Cat No.	Latching cover ceiling roses, 240V a.c. Colour codes, BL (Black), WE (White).
10	80	(WE) Ceiling rose, 4 way connection. Easily wired with connectors supplied. 68mm dia x 44mm high.
10	84	Screw-on cover ceiling roses, 240V a.c. Size: 65mm dia x 37mm high. Ceiling rose 10A, 4 plate x 2 post per plate (BL, BR, WE)
10	78	Large screw-on cover type, 240V a.c. Size: 92mm dia x 36mm high. Ceiling rose 10A, 4 plate x 2 posts per plate (WE)

Battenholders



Pack	Cat No.	240V. a.c. To suit B22 bayonet cap lamps. Supplied with long skirt, (Cat. No. 333SK). Battenholder, 4 terminals
10	360	Adjustable angle battenholder, 4 large terminals. 64mm dia base. 50mm mounting centres. (WE)
5	360/W1	Adjustable angle battenholder, IP23. 4 terminals. Integral anchor plugs. 50mm mounting centres. (WE)
10	366	Battenholder, 4 terminals, standard 68mm dia base. 50mm mounting centres. (WE)
10	366Y	Battenholder, 4 terminals, integral fix-fast anchor plugs, standard 68mm dia base. 50mm mounting centres. (WE)
10	366LY	Battenholder, 4 terminals, separate fix-fast anchor plugs, standard 68mm dia base. 50mm mounting centres. (WE)
10	368	Battenholder, 4 terminals, 90mm dia base. 50mm mounting centres. (WE)
10	368/1	Battenholder, 4 terminals, 90mm dia base. 70mm mounting centres. (WE)

Lampholders



Pack	Cat No.	BC cord grip, 240V. Colour codes: BL (Black), WE (White)
10	333	Lampholder, cord grip, supplied with long skirt, (Cat. No. 333SK) (BL, WE)

Plugs, Bases, Sockets & Lampholders



Pack	Cat No.	Tapered cap - top cable entry
		Supplied with long skirt, (Cat. No. 333SK)
10	359/10	Lampholder with 10 mm thread (1.0 mm pitch) (BR, BL, WE)



Pack	Cat No.	Tapered cap - side cable entry
		Supplied with long skirt, (Cat. No. 333SK). Threaded hole is blind for insulation from terminal area.
10	359A10	Lampholder with 10mm thread (1.0mm pitch) (WE)



Pack	Cat No.	Switched lampholders - tapered cap - top cable entry
		240V a.c. Double pole push bar switch with red dot indication. Supplied with long skirt, (Cat. No. 333SK).
10	310	Switched lampholder with 1/2 inch brass thread with nipple (WE)
10	310/10	Switched lampholder with 10mm thread (1.0mm pitch) (WE)



Pack	Cat No.	Festoon lampholders
		Mounting centres: 50mm. 3A, 240V a.c.. BC with side entry cable, wire piercing connections. Overall height 65mm.
10	303/1F	Lampholder with fanged screw-on cap & long skirt, (Cat. No. 333SK) (BL)
10	WS303/1R	Lampholder with round screw-on cap & rubber skirt for weatherproofing (BL)
10	WS303/1F	Lampholder with fanged screw-on cap & rubber skirt for weatherproofing (BL)

Lampholder accessories



Pack	Cat No.	Lampholder skirts
10	A1801	Lampholder skirt (short), 24mm (WE)
10	A5625	Lampholder skirt (medium), 30mm (WE)
10	333SK	Lampholder skirt (long), 37 mm (WE)