

## Kabelverschraubungen

## Cable Glands

### WAZU-M/EX

Material: Messing vernickelt  
 Klemmeinsatz: PA  
 Dichtung: NBR  
 O-Ring: NBR  
 Einsatztemperatur: -20 °C bis 95 °C  
 Schutzart: IP 68

Material: brass, nickel-plated  
 Clamping insert: PA (Nylon)  
 Sealing insert: NBR  
 O-ring: NBR  
 Temperature range: -20 °C to 95 °C  
 Protection type: IP 68

154.10

154.30

Zertifikat: DMT 03 ATEX E 051 X

Certificate: DMT 03 ATEX E 051 X



Gewinde Entry Thread G	mm	mm	H mm	Gew. kurz / Thread short		Gew. lang / Thread long	
				GL mm	No.	GL mm	No.
M 12 x 1,5	2 - 5	14	19	5	154.1505.10	10	154.1505.30
	3 - 6,5				154.1507.10		154.1507.30
M 16 x 1,5	2 - 6	19/17	21	6	154.1706.10	10	154.1706.30
	4 - 8				154.1708.10		154.1708.30
M 20 x 1,5	6 - 10	20	22	6	154.1710.10	10	154.1710.30
	5 - 9	22	23	6	154.2009.10	10	154.2009.30
	6 - 12				154.2012.10		154.2012.30
	10 - 14	24	24	6	154.2014.10	10	154.2014.30
M 25 x 1,5	10 - 16	30	25	7	154.2516.10	12	154.2516.30
	14 - 18				154.2518.10		154.2518.30
M 32 x 1,5	13 - 20	40	31	8	154.3220.10	12	154.3220.30
	20 - 25				154.3225.10		154.3225.30
M 40 x 1,5	20 - 26	50	37	8	154.4026.10	15	154.4026.30
	22 - 32				154.4032.10		154.4032.30
M 50 x 1,5	25 - 31	57	37	9	154.5031.10	15	154.5031.30
	32 - 38				154.5038.10		154.5038.30
M 63 x 1,5	29 - 35	68/64	38	10	154.6335.10	15	154.6335.30
	37 - 44				154.6344.10		154.6344.30
Pg 7	2 - 5	14	19	5	154.0705.10	10	154.0705.30
	3 - 6,5				154.0707.10		154.0707.30
Pg 9	2 - 6	17	21	6	154.0906.10	10	154.0906.30
	4 - 8				154.0908.10		154.0908.30
Pg 11	3 - 7	20	22	6	154.1107.10	10	154.1107.30
	6 - 10				154.1110.10		154.1110.30
Pg 13,5	5 - 9	22	23	6,5	154.1309.10	10	154.1309.30
	6 - 12				154.1312.10		154.1312.30
Pg 16	7 - 12	24	24	6,5	154.1612.10	10	154.1612.30
	10 - 14				154.1614.10		154.1614.30
Pg 21	10 - 16	30	25	7	154.2116.10	12	154.2116.30
	14 - 18				154.2118.10		154.2118.30
Pg 29	13 - 20	40	31	8	154.2920.10	12	154.2920.30
	20 - 25				154.2925.10		154.2925.30
Pg 36	20 - 26	50	37	8	154.3626.10	15	154.3626.30
	22 - 32				154.3632.10		154.3632.30
Pg 42	25 - 31	57	37	9	154.4231.10	15	154.4231.30
	32 - 38				154.4238.10		154.4238.30
Pg 48	29 - 35	64	38	10	154.4835.10	15	154.4835.30
	37 - 44				154.4844.10		154.4844.30
3/8" NPT	2 - 6	19/17	21	15	154.3906.10		
	4 - 8				154.3908.10		
1/2" NPT	5 - 9	24/22	24	13	154.1909.10		
	6 - 12				154.1912.10		
3/4" NPT	10 - 16	30	25	13	154.3516.10		
	14 - 18				154.3518.10		
1" NPT	13 - 20	40	31	19	154.7520.10		
	20 - 25				154.7525.10		

