

## Kabelverschraubungen

## Cable Glands

### WAZU-S/EX

Material: Edelstahl (1.4305)  
 Klemmeinsatz: PA  
 Dichtung: NBR  
 O-Ring: NBR  
 Einsatztemperatur: -20 °C bis 95 °C  
 Schutzart: IP 68



Material: stainless steel (1.4305)  
 Clamping insert: PA (Nylon)  
 Sealing insert: NBR  
 O-ring: NBR  
 Temperature range: -20 °C to 95 °C  
 Protection type: IP 68

**156.10**

Zertifikat: DMT 03 ATEX E 051 X

Certificate: DMT 03 ATEX E 051 X



Gewinde Entry Thread G	 mm	 mm	H mm	GL mm	No.
M 12 x 1,5	2 - 5	14	19	5	156.1505.10
	3 - 6,5				156.1507.10
M 16 x 1,5	3 - 7	22	22	6	156.1707.10
	5 - 10				156.1710.10
M 20 x 1,5	7 - 12	24	24	6	156.2012.10
	10 - 14				156.2014.10
M 25 x 1,5	9 - 16	30	25	7	156.2516.10
	13 - 18				156.2518.10
M 32 x 1,5	13 - 20	41	31	8	156.3220.10
	20 - 25				156.3225.10
M 40 x 1,5	20 - 26	50	37	8	156.4026.10
	22 - 32				156.4032.10
Pg 7	2 - 5	14	19	5	156.0705.10
	3 - 6,5				156.0707.10
Pg 9	2 - 6	17	21	6	156.0906.10
	4 - 8				156.0908.10
Pg 11	3 - 7	22	22	6	156.1107.10
	5 - 10				156.1110.10
Pg 13,5	5 - 9	22	23	6,5	156.1309.10
	6 - 12				156.1312.10
Pg 16	7 - 12	24	24	6,5	156.1612.10
	10 - 14				156.1614.10
Pg 21	9 - 16	30	25	7	156.2116.10
	13 - 18				156.2118.10
Pg 29	13 - 20	41	31	8	156.2920.10
	20 - 25				156.2925.10
Pg 36	20 - 26	50	37	8	156.3626.10
	22 - 32				156.3632.10

