


## Explosionproof and Dust-tight Fittings and Accessories


### EXPLOSIONPROOF AND DUST-TIGHT SHORT RADIUS PULL ELBOWS CLASS I, GROUP D; CLASS II, GROUPS E, F & G; NEMA 7 & 9



FL



MFL



This versatile and inexpensive explosion-proof fitting with a threaded cover will easily and compactly handle 90° conduit runs. FL series have two female entrances. MFL series has one female entrance and one removable threaded nipple.

Catalog Number	Conduit Size (In.)	Nominal Dimensions Inches			Standard Package	
		A	B	C	Quantity	Weight Pounds
FL92	1/2	2-5/8	2-1/8	1-3/8	25	8
FL93	3/4	2-13/16	2-1/8	1-1/2	25	10-1/2
FL94	1	3-1/4	2-7/16	1-7/8	25	11
FL95	1-1/4	3-3/4	3-1/2	2-1/4	25	24
*FL96	1-1/2	4-5/8	4-3/16	2-5/8	25	30
MFL92	1/2	2-5/8	2-1/8	1-3/8	25	9
MFL93	3/4	2-13/16	2-1/8	1-1/2	25	12
MFL94	1	3-1/4	2-7/16	1-7/8	25	13
MFL95	1-1/4	3-3/4	3-1/2	2-1/4	25	26
*MFL96	1-1/2	4-5/8	4-3/16	2-5/8	25	34

#### Compliances

- NEC Class I, Group D  
Class II, Groups E, F, G
- UL Standard 886 - CSA Standard C22.2 No. 30

\* Fitting not UL Listed or CSA Certified



CSA Certified LR27991



UL Listed E10493

### EXPLOSIONPROOF AND DUST-TIGHT REMOVABLE PLUGS CLASS I, GROUPS A, B, C & D; CLASS II, GROUPS E, F & G; NEMA 7 & NEMA 9

Tapered thread close-up plugs for explosionproof conduit entrances. Provides 5 full threads of engagement. Made of aluminum alloy, these plugs have screw-driver slots and fit practically flush when installed.



OX

Catalog Number	Conduit Size (In.)	Standard Package		Catalog Number	Conduit Size (In.)	Standard Package	
		Qty	Weight Pounds			Qty	Weight Pounds
OX2	1/2	250	6-3/4	OX8	2	50	12
OX3	3/4	250	10-1/4	OX10	2-1/2	50	20-1/2
OX4	1	150	9	OX12	3	50	30
OX5	1-1/4	100	12	OX14	3-1/2	50	40
OX6	1-1/2	100	14-1/2	OX16	4	50	52