


Explosionproof and Dust-tight Fittings and Accessories

**EXPLOSIONPROOF AND DUST-TIGHT CONDUIT UNIONS
CLASS I, GROUPS A, B, C & D;
CLASS II, GROUPS E, F & G; NEMA 7 & NEMA 9**


Explosionproof unions for use in conduit piping systems for ease of installation and removal of fittings, boxes and equipment enclosures in hazardous atmosphere areas. Parts are steel, cadmium plated for corrosion protection. Style XU has two female NPT threads. Style XUM has two female NPT threads and one plated threaded nipple.



XU



XUM



Catalog Number	Conduit Size		Standard Package	
			Qty	Weight Pounds
XU2	1/2"	Female-Female	50	19
XU3	3/4"	Female-Female	50	21
XU4	1"	Female-Female	25	13-1/2
XUM2	1/2"	Female-Male	50	22
XUM3	3/4"	Female-Male	50	26
XUM4	1"	Female-Male	25	16-1/2

DIMENSIONS

	Conduit Size	A	B
Series	1/2"	1-3/4"	1-1/2"
XU	3/4"	1-3/4"	1-3/4"
	1"	1-15/16"	2"
Series	1/2"	2-9/16"	1-1/2"
XUM	3/4"	2-3/4"	1-3/4"
	1"	3"	2"

- CSA Certified LR27991
- UL Listed E10493

Compliance

- NEC Class I, Groups A, B, C, D
Class II, Groups E, F, G
- UL Standard 886 - CSA Standard C22.2 No.30