

## Germany / Europe - Angle Mains Line Plugs, Side Cable Entry

Mains line plug with earthing contact, additional earthing socket, lateral cable entry point and die-injected strain relief sleeve

*Stecker mit seitlichem Schutzkontakt, zweitem Schutzkontaktsystem, seitlicher Kabeleinführung und angespritzter Knickschutztüle*



577 WH

### SPECIFICATIONS

- Electrical Ratings: 250V AC, 16A
- Standards according to: DIN VDE 0620-1:2005, DIN 49 441 Part 1
- Material & Type of Terminals: CuZn 37/39 (screw terminals)
- Material of Housing and Carrying Parts: Polypropylene
- RoHS COMPLIANT 2002/96/EC

Catalog No.	Color	Description	VPE/Pack	EDP-No.
<b>577 WH</b>	White	Angle Mains Line Plug (1.5mm <sup>2</sup> max.)	50	<b>124623</b>
<b>577 BK</b>	Black	Angle Mains Line Plug (1.5mm <sup>2</sup> max.)	50	<b>124622</b>
<b>577 WH 2</b>	White	Angle Mains Line Plug (2.5mm <sup>2</sup> max.)	50	<b>122274</b>
<b>577 BK 2</b>	Black	Angle Mains Line Plug (2.5mm <sup>2</sup> max.)	50	<b>124621</b>

**Notes:** Rewireable, for supply line H05VV-F 3 x 1,0 mm<sup>2</sup> and 3 x 1,5 mm<sup>2</sup>, or 3 x 2,5 mm<sup>2</sup> max.

*Wiederanschließbare Ausführung für flexible Leiter H05VV-F 3 x 1,0 mm<sup>2</sup> und 3 x 1,5 mm<sup>2</sup>, oder 3 x 2,5 mm<sup>2</sup> max.*

