


## HSK-K-PVDF

## Metr./NPT



Material  
Seal  
Protection

PVDF  
FPM  
IP 68 – 10 bar (NEMA 6 – 150 PSIG)  
within the specified clamping range  
only with optional O-Ring  
(see page 122)



Operating  
Temperature  
Colors

-35 °C – 150 °C (-31 °F – 302 °F)  
natural

Other colors available upon request

AG	ØK mm	GL mm	H mm	 mm	Number
M 12 x 1,5	3 - 6,5	8	21	15	1.299.1200.50
M 12 x 1,5	2 - 5	8	21	15	1.299.1200.51
M 16 x 1,5	4 - 8	8	22	19	1.299.1600.50
M 16 x 1,5	2 - 6	8	22	19	1.299.1600.51
M 20 x 1,5	6 - 12	9	27	24	1.299.2000.50
M 20 x 1,5	5 - 9	9	27	24	1.299.2000.51
M 25 x 1,5	13 - 18	11	31	33	1.299.2500.50
M 25 x 1,5	9 - 16	11	31	33	1.299.2500.51
M 32 x 1,5	18 - 25	11	39	42	1.299.3200.50
M 32 x 1,5	13 - 20	11	39	42	1.299.3200.51
3/8" NPT	4 - 8	15	22	22/19	1.299.3800.70
3/8" NPT	2 - 6	15	22	22/19	1.299.3800.71
1/2" NPT	6 - 12	13	27	24	1.299.1200.70
1/2" NPT	5 - 9	13	27	24	1.299.1200.71
1/2" NPT/16	10 - 14	13	28	27	1.299.1216.70
1/2" NPT/16	7 - 12	13	28	27	1.299.1216.71
3/4" NPT	13 - 18	14	31	33	1.299.3400.70
3/4" NPT	9 - 16	14	31	33	1.299.3400.71

