


HSK-M-PVDF

Metr./NPT



Material: Nickel plated brass
 Clamping insert: PVDF
 Seal: FPM
 O-Ring: FPM
 Protection: IP 68 – 10 bar within the specified clamping range
 Operating Temperature: -35 °C – 150 °C (-31 °F – 302 °F)



AG	∅k mm	GL mm	H mm	 mm	Number	GL mm	Number elongated
M 12 x 1,5	3 - 6,5	5	19	14	1.699.1200.50	10	1.699.1200.30
M 12 x 1,5	2 - 5	5	19	14	1.699.1200.51	10	1.699.1200.31
M 16 x 1,5	5 - 10	6	22	20	1.699.1600.50	10	1.699.1600.30
M 16 x 1,5	3 - 7	6	22	20	1.699.1600.51	10	1.699.1600.31
M 20 x 1,5	10 - 14	6	24	24	1.699.2000.50	10	1.699.2000.30
M 20 x 1,5	7 - 12	6	24	24	1.699.2000.51	10	1.699.2000.31
M 25 x 1,5	13 - 18	7	26	30	1.699.2500.50	12	1.699.2500.30
M 25 x 1,5	9 - 16	7	26	30	1.699.2500.51	12	1.699.2500.31
M 32 x 1,5	18 - 25	8	31	40	1.699.3200.50	12	1.699.3200.30
M 32 x 1,5	13 - 20	8	31	40	1.699.3200.51	12	1.699.3200.31
M 40 x 1,5	22 - 32	8	37	50	1.699.4000.50	15	1.699.4000.30
M 40 x 1,5	20 - 26	8	37	50	1.699.4000.51	15	1.699.4000.31
3/8" NPT	4 - 8	15	21	17 / 19	1.699.3800.70		
3/8" NPT	2 - 6	15	21	17 / 19	1.699.3800.71		
1/2" NPT	6 - 12	13	24	22 / 24	1.699.1200.70		
1/2" NPT	5 - 9	13	24	22 / 24	1.699.1200.71		
3/4" NPT	13 - 18	13	25	30	1.699.3400.70		
3/4" NPT	9 - 16	13	25	30	1.699.3400.71		

