

RE-MS

Threaded Adapters

Metric / PG / NPT



Configuration

Adapter
External Thread

Internal Thread

Properties

Temperature Range
Protection Grade

Nickel Plated Brass
Metric as per EN 60423
or PG as per DIN 40430
NPT

Adapter from Metric or PG to
NPT-threaded holes

up to +200°C
Dependent on the combination
with other components.



	Catalog Number	AG	IG	GL mm	H mm	D mm	SW mm
	1.171.1612.50	M 16 x 1.5	1/2 NPT	6	17	—	24
	1.171.2012.50	M 20 x 1.5	1/2 NPT	6	17	—	24
	1.171.2512.50	M 25 x 1.5	1/2 NPT	7	8	—	30
	1.171.2534.50	M 25 x 1.5	3/4 NPT	7	19	—	30
	1.171.3210.50	M 32 x 1.5	1 NPT	8	25	—	40
	1.171.3254.50	M 32 x 1.5	1 1/4 NPT	8	25	—	46
	1.171.1112.01	PG 11	1/2 NPT	6	16.7	—	24
	1.171.1312.01	PG 13.5	1/2 NPT	6.5	17	—	24
	1.171.1612.01	PG 16	1/2 NPT	6.5	16.5	—	24
	1.171.2112.01	PG 21	1/2 NPT	7	8	—	30
1.171.2134.01	PG 21	3/4 NPT	7	17	—	30	
1.171.2910.01	PG 29	1 NPT	8	12	—	40	