

## Wireway – Oiltight Raintight and Raintight Trough Class 5120, 5130, 5140



### Oiltight –NEMA Type 12

Type "LJ" Oiltight Lay-in Wireway is fully gasketed and used to protect runs of electrical wiring from oil, water, coolants, dirt or dust as well as physical damage. This wireway is manufactured to exceed oiltight and NFPA standards for Industrial Control Equipment. Lengths and fittings are made of 14 gauge steel with 10 gauge end flanges. Straight lengths and fittings have hinged covers with oil resistant neoprene gasket all around and are held closed with pull down latches. All lengths and fittings are without knockouts. Type LJ Lay-in Wireway is finished with ANSI-49 gray epoxy paint applied by a cathodic electrodeposition paint process over a corrosion resistant phosphate preparation. All Type LJ oiltight wireway is UL listed, File No. E6625 as steel enclosed wireway and auxiliary gutter. Conforms to NEMA Type 12.

### Type LJ Lay-in Wireway★

Description	2½" x 2½"		4" x 4"		6" x 6"		8" x 8"		12" x 12"	
	Catalog No.	Price	Catalog No.	Price	Catalog No.	Price	Catalog No.	Price	Catalog No.	Price
STRAIGHT LENGTHS –										
3" Nipple	LJ203		LJ403		LJ603		LJ803		LJ1203	
6" Nipple	LJ206		LJ406		LJ606		LJ806		LJ1206	
1 Foot	LJ21		LJ41		LJ61		LJ81		LJ121	
2 Foot	LJ22		LJ42		LJ62		LJ82		LJ122	
3 Foot	LJ23		LJ43		LJ63		LJ83		LJ123	
4 Foot	LJ24		LJ44		LJ64		LJ84		LJ124	
5 Foot	LJ25		LJ45		LJ65		LJ85		LJ125	
10 Foot△	LJ210		LJ410		LJ610		LJ810		....	....
ELBOWS –										
45° Inside Opening	LJ245LI		LJ445LI		LJ645LI		LJ845LI		LJ1245LI	
45° Outside Opening	LJ245LO		LJ445LO		LJ645LO		LJ845LO		LJ1245LO	
45° Top Opening	LJ245LT		LJ445LT		LJ645LT		LJ845LT		LJ1245LT	
90° Inside Opening	LJ290LI		LJ490LI		LJ690LI		LJ890LI		LJ1290LI	
90° Outside Opening	LJ290LO		LJ490LO		LJ690LO		LJ890LO		LJ1290LO	
90° Top Opening	LJ290LT		LJ490LT		LJ690LT		LJ890LT		LJ1290LT	
Cross	LJ2X		LJ4X		LJ6X		LJ8X		LJ12X	
Tee-Top Opening	LJ2TT		LJ4TT		LJ6TT		LJ8TT		LJ12TT	
Tee-Outside Opening	LJ2TO		LJ4TO		LJ6TO		LJ8TO		LJ12TO	
Swivel Fitting	LJ2S		LJ4S		LJ6S		LJ8S		LJ12S	
Closing Plate	LJ2CP		LJ4CP		LJ6CP		LJ8CP		LJ12CP	
Panel Adapter	LJ2A		LJ4A		LJ6A		LJ8A		LJ12A	
Reducer	....		LJ42R		LJ64R		LJ86R		LJ128R	
Cut-Off Fitting	LJ2CF		LJ4CF		LJ6CF		LJ8CF		LJ12CF	
Telescopic Fitting	LJ2TF		LJ4TF		LJ6TF		LJ8TF		LJ12TF	
Transposition FTG-CW	LJ21CW		LJ41CW		LJ61CW		LJ81CW		....	
Transposition FTG-CCW	LJ21CCW		LJ41CCW		LJ61CCW		LJ81CCW		....	
Transposition Elbow-CW	LJ290LCW		LJ490LCW		LJ690LCW		LJ890LCW		....	
Transposition Elbow-CCW	LJ290LCCW		LJ490LCCW		LJ690LCCW		LJ890LCCW		....	
LJ to LC Adapter	LJ2LC		LJ4LC		LJ6LC		LJ8LC		LJ12LC	
Drop Hanger	LJ2DH		LJ4DH		LJ6DH		LJ8DH		LJ12DH	
Bracket Hanger	LJ2BH		LJ4BH		LJ6BH		LJ8BH		LJ12BH	
90° Connector	LJ290C		LJ490C		LJ690C		LJ890C		LJ1290C	
Extra Connector Kit	LJ2C		LJ4C		LJ6C		LJ8C		LJ12C	
5' 0" Barrier/Partition	....		LD45B		LD65B		LD85B		LD125B	
Flexible Fitting	....		LJ4FF		LJ6FF		....		....	

△ 10 Foot straight lengths UL listed for up to 10 foot hanger spacing.  
★ Connector kit furnished with each length and fitting.



### Raintight Wireway—NEMA Type 3R

Outdoor raintight gangable wireway is used to protect electrical wiring against rain, sleet and physical damage. Unique drip shield cover protects wiring from weather and maintains the "lay-in" feature for ease of wiring installation. Lengths and fittings constructed of 16 gauge galvalneal steel with ANSI-49 gray epoxy paint applied by a cathodic electrodeposition paint process over a corrosion resistant phosphate preparation. Underwriters Laboratories Listed, File No. E6625 as steel enclosed wireway and auxiliary gutter (horizontal mounting only). Conforms to NEMA Type 3R.



### Raintight Trough—NEMA Type 3R

Raintight Trough is designed for ganging meter devices, panelboards, switches and circuit breaker enclosures. Each length is a completely enclosed section with a removable cover that has provisions for sealing.

**Design:** 4 and 6 inch wireway is constructed of 16 gauge galvalneal steel. 8 and 12 inch wireway is constructed of 14 gauge galvalneal steel. All Raintight Troughs conform to NEMA Type 3R.

**Finish:** ANSI-49 gray epoxy paint applied by a cathodic electrodeposition paint process over a corrosion resistant phosphate preparation. All Raintight Troughs are Underwriters Laboratories Listed, File No. E6625 as steel enclosed wireway and auxiliary gutter (horizontal mounting only).

### Raintight Lay-In Wireway

Description	4" x 4"		6" x 6"	
	Catalog Number	Price	Catalog Number	Price
1 Ft. Length	LDR41		LDR61	
5 Ft. Length	LDR45		LDR65	
10 Ft. Length	LDR410		LDR610	
90° Elbow	LDR490L		LDR690L	
Tee	LDR4T		LDR6T	
Junction Box	LDR4J		LDR6J	
Panel Adapter	LDR44A		LDR66A	
Closing Plate	LDR4CP		LDR6CP	
Gusset Bracket	LD4GB		LD6GB	
5'0" Barrier/Partition	LD45B		LD65B	

### Raintight Trough Enclosures

Description	4" x 4"		6" x 6"		8" x 8"		12" x 12"	
	Cat. No.	Price	Cat. No.	Price	Cat. No.	Price	Cat. No.	Price
1 Foot Length	RD41		RD61		....	....	....	....
2 Foot Length	RD42		RD62		RD82		RD122	
3 Foot Length	RD43		RD63		RD83		RD123	
4 Foot Length	RD44		RD64		RD84		RD124	
5 Foot Length	RD45		RD65		RD85		RD125	
6 Foot Length	RD46		RD66		RD86		RD126	
10 Foot Length	RD410		RD610		RD810		RD1210	