

## Circuit Breakers

## For I-Line® Panelboards and Switchboards

Class 660, 665, 670, 830



**LA/LH**  
2- and 3-pole  
6 in (152 mm)  
Mounting Height

**Table 9.112: L-frame—400 A, I-Line® LA/LH MC High Magnetic Withstand Circuit Breaker For Mission Critical Loads**

Ampere Rating	AC Magnetic Level Factory Set ■	Standard Interrupting		High Interrupting		Terminal Wire Range
		Catalog Number	\$ Price	Catalog Number	\$ Price	
<b>3-pole, 480 Vac, LA/LH MC Circuit Breaker</b>						
200	4000	LA34200MC		LH34200MC		AL250LA (1) #4 AWG–350 kcmil
225	4500	LA34225MC		LH34225MC		
250	5000	LA34250MC		LH34250MC		
400	8000	LA34400MC		LH34400MC		AL400LA (1) #1 AWG–600 kcmil or (2) #1 AWG–250 kcmil

**Table 9.113: L-frame—400 A, Thermal-magnetic (600 Vac)**

Ampere Rating	AC Magnetic Trip Settings		Standard Interrupting		High Interrupting		Terminal Wire Range
	Low	High	Catalog Number	\$ Price	Catalog Number	\$ Price	
<b>2-pole, 600 Vac, 250 Vdc▲</b>							
125	625	1250	LA26125( )		LH26125( )		AL400LA (1) #1 AWG–600 kcmil or (2) #1 AWG–250 kcmil
150	750	1500	LA26150( )		LH26150( )		
175	875	1750	LA26175( )		LH26175( )		
200	1000	2000	LA26200( )		LH26200( )		
225	1125	2250	LA26225( )		LH26225( )		
250	1250	2500	LA26250( )		LH26250( )		
300	1500	3000	LA26300( )		LH26300( )		
350	1750	3500	LA26350( )		LH26350( )		
400	2000	4000	LA26400( )		LH26400( )		
<b>3-pole, 600 Vac, 250 Vdc</b>							
125	625	1250	LA36125		LH36125		AL400LA (1) #1 AWG–600 kcmil or (2) #1 AWG–250 kcmil
150	750	1500	LA36150		LH36150		
175	875	1750	LA36175		LH36175		
200	1000	2000	LA36200		LH36200		
225	1125	2250	LA36225		LH36225		
250	1250	2500	LA36250		LH36250		
300	1500	3000	LA36300		LH36300		
350	1750	3500	LA36350		LH36350		
400	2000	4000	LA36400		LH36400		



**LI**  
2- and 3-pole  
7.5 in (190 mm)  
Mounting Height

**Table 9.114: L-frame—600 A, Thermal-magnetic (600 Vac)**

Ampere Rating	AC Magnetic Trip Settings		Extra High Interrupting		Current Limiting		Terminal Wire Range
	Low	High	Catalog Number	\$ Price	Catalog Number	\$ Price	
<b>2-pole, 600 Vac▲</b>							
300	1500	3000	LC26300( )		LI26300( )		AL600LI5 (2) #4/0 AWG–500 kcmil
350	1750	3500	LC26350( )		LI26350( )		
400	2000	4000	LC26400( )		LI26400( )		
450	2250	4500	LC26450( )		LI26450( )		AL600LI5 (2) #4/0 AWG–500 kcmil
500	2500	5000	LC26500( )		LI26500( )		
600	3000	5400	LC26600( )		LI26600( )		
<b>3-pole, 600 Vac</b>							
300	1500	3000	LC36300		LI36300		AL600LI5 (2) #4/0 AWG–500 kcmil
350	1750	3500	LC36350		LI36350		
400	2000	4000	LC36400		LI36400		
450	2250	4500	LC36450		LI36450		AL600LI5 (2) #4/0 AWG–500 kcmil
500	2500	5000	LC36500		LI36500		
600	3000	5400	LC36600		LI36600		

- ▲ 2-pole circuit breaker catalog numbers are completed by adding required phase connection letters as suffix to catalog number.
- AC magnetic setting tolerances are +0 -25% from maximum value shown.



**LC**  
2- and 3-pole  
7.5 in (190 mm)  
Mounting Height

**Table 9.115: Interrupting Ratings (kA)**

	LA	LH	LC	LI
240 V	42	65	100	200
480 V	30	35	65	200
600 V	22	25	35	100