

## Australia / New Zealand - Made-to-Order Power Supply Cords

### SPECIFICATIONS

- Molded PVC male plug.
- Straight, with flex strain relief.
- Plug Standard: AS 3112
- Standard bulk packaged
- Approvals: SAA
- Molded PVC over nylon insert, straight male grounding plug with flex type strain relief. Nickel-plated brass solid blades.



**YP-36**

Molded Plug without Grounding Pin AS 3112, with or without Connector see below

Standard: Australia AS/NZS 3112 without ground pin  
 Rating: 10A/250V AC  
 Wire Type: H05VV-F 0.75mm<sup>2</sup>  
 H05VV-F 1.00mm<sup>2</sup>  
 Approval: SAA



**YC-13**

Standard: IEC 60320/C7 (Standard Sheet 7)  
 Rating: 2.5A/250V AC  
 Wire Type: H03VVH2-F 0.75mm<sup>2</sup>  
 H03VVH2-F 0.75mm<sup>2</sup>  
 Approval: SAA



**YC-13L**

Standard: IEC 60320/C7 (Standard Sheet 7)  
 Rating: 2.5A/250V AC  
 Wire Type: H03VVH2-F 0.75mm<sup>2</sup>  
 H03VVH2-F 0.75mm<sup>2</sup>  
 Approval: SAA

To learn more about B-I-A please visit us at our  
 WEB site: [www.BiaGmbH.com](http://www.BiaGmbH.com)



## Australia / New Zealand - Made-to-Order Power Supply Cords

### SPECIFICATIONS

- Molded PVC male grounding plug.
- Straight, with flex strain relief.
- Plug Standard: AS 3112
- Standard bulk packaged
- Approvals: SAA
- Molded PVC over nylon insert, straight male grounding plug with flex type strain relief. Nickel-plated brass solid blades.



Standard: Australia AS/NZS 3112  
 Rating: 10A/250V AC  
 Wire Type: H05VV-F 0.75mm<sup>2</sup>  
 H05VV-F 1.00mm<sup>2</sup>  
 Approval: SAA



Standard: IEC 60320/C13  
 Rating: 10A/250V AC  
 Wire Type: H05VV-F 0.75mm<sup>2</sup> x 3C  
 H05VV-F 1.00mm<sup>2</sup> x 3C  
 Approval: SAA



Standard: IEC 60320/C13  
 Rating: 10A/250V AC  
 Wire Type: H05VV-F 0.75mm<sup>2</sup> x 3C  
 H05VV-F 1.00mm<sup>2</sup> x 3C  
 Approval: SAA

To learn more about B-I-A please visit us at our  
 WEB site: [www.BiaGmbH.com](http://www.BiaGmbH.com)



## Australia / New Zealand - Made-to-Order Power Supply Cords

### SPECIFICATIONS

- Molded PVC male grounding plug.
- Straight, with flex strain relief.
- Plug Standard: AS 3112
- Standard bulk packaged
- Approvals: SAA
- Molded PVC over nylon insert, straight male grounding plug with flex type strain relief. Nickel-plated brass solid blades.



Standard: Australia AS/NZS 3112  
 Rating: 10A/250V AC  
 Wire Type: H05VV-F 0.75mm<sup>2</sup>  
 H05VV-F 1.00mm<sup>2</sup>  
 Approval: SAA



Standard: IEC 60320/C5  
 Rating: 10A/250V AC  
 Wire Type: H05VV-F 0.75mm<sup>2</sup> x 3C  
 H05VV-F 1.00mm<sup>2</sup> x 3C  
 Approval: SAA



Standard: AS/NZS 3112 Receptacle  
 Rating: 10A/250V AC  
 Wire Type: H05VV-F 0.75mm<sup>2</sup> x 3C  
 H05VV-F 1.00mm<sup>2</sup> x 3C  
 Approval: SAA

\* Angle Plug No. YC-14L available on Request.

To learn more about B-I-A please visit us at our  
 WEB site: [www.BiaGmbH.com](http://www.BiaGmbH.com)

