

## B□□△ Product Information

## Australia/New Zealand - Rewireable Plugs, AS/NZS, 10 Amp.

Rewireable Cord Plugs, 2 Pole 3 Wire Grounding, 10 Amp.

Wiederanschliessbare Stecker, 10 Amp.

## **SPECIFICATIONS**

- Ratings: 10 Amp, 250 Volts AC
- 2 Pole 3 Wire Grounding (2P + E)
- Plugs according to: AS/NZS 3112:2000 (with Insulated Active and Neutral Pins)
- Screw-Type Terminals
- Thermoplastic, Galvanized Brass Contacts
- Standard Colors: Black, White



**90WE** 10A, 250V AC

Catalog No.	Color	Description	Weight/each	VPE/Pack	EDP No.
90BL	Black	Cord Plug, 10A, 250V AC, 3 Pin Flat	34 g net.	500/10	118216
90GY*	Gray	Cord Plug, 10A, 250V AC, 3 Pin Flat	34 g net.	500/10	121075
90WE	White	Cord Plug, 10A, 250V AC, 3 Pin Flat	34 g net.	500/10	121074
90RWE	White	Cord Plug, 10A, 250V AC, Flat Active/Neutral, Round Earth	39 g net.	500/10	109412


90 Series 3 Pin Flat

## **NOTES:**

Join Standard Cordage only, Cross Section from  $0.75 \text{ to } 1.0 \text{ mm}^2 (2P + E)$ max. 10A/250V AC.


Connections specified by the appliance or product.

Warning: The load can not exceed the specifications written in the products.



90R Series


Round Earth




3 Pin Flat:

Active, Neutral, Earth





maximum cordage diameter Ø 8.6 mm



Flat Active and Neutral, Round Earth

Technical Data are Subject to Change without Notice. Dimensions in mm.

<sup>\*</sup> If existing stock is depleted, item will be discontinued.