

**SPECIFICATIONS, 60 Amp Holders**

- Base, High Impact Thermoplastic, 125°C
- Class J Holders Have been Tested and Approved for 200,000 Amp Interrupting Capacity
- Patented Cool Clip® Design
- Clip, Copper Alloy, Tin Plated
- UL Listed and CSA Certified
- Reinforcing Member Available

100 and 200 Amp Holders

- Base, General Purpose Phenolic, Fabricated
- Class J Holders Have been Tested and Approved for 200,000 Amp Interrupting Capacity
- Patented Cool Clip® Design
- Clip, One Piece Aluminum with Copper Spring, Tin Plated
- UL Listed and CSA Certified

Class J Fuse Holders 600Vac

| | |
|------|--------|
| 31- | 60Amp |
| 61- | 100Amp |
| 101- | 200Amp |

Fuse Size:

| |
|--------------------|
| (Ø 27.0 x 60.3)mm |
| (Ø 28.6 x 117.5)mm |
| (Ø 38.1 x 146.1)mm |

Dimensions for 100Amp and 200Amp Holders upon Request
Fuse Holders up to 600Amp upon Request

| No. of Poles | Cat.No. Class J Standard | Reinforced | Wire Connector | Copper Wire Range (AWG) | UPE Packed |
|--------------|--------------------------|------------|----------------|-------------------------|------------|
| 1 | 6J 60A 1B | R6J 60A 1B | Box | 2 - 14 | 50 |
| 2 | 6J 60A 2B | R6J 60A 2B | Box | 2 - 14 | 25 |
| 3 | 6J 60A 3B | R6J 60A 3B | Box | 2 - 14 | 20 |
| 1 | 6J 100A 1B | | Box | 2/0 - 14 | 20 |
| 3 | 6J 100A 3B | | Box | 2/0 - 14 | 10 |
| 1 | 6J 200A 1B | | Box | 250MCM-6AWG | 5 |
| 3 | 6J 200A 3B | | Box | 250MCM-6AWG | 2 |